Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name LP 163/93
- **UFI**: 00NF-M0QT-F001-S7RX
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Cleaning material/ Detergent

Restrictions on use apply to this product according to Regulation (EU) no. 1907/2006 Annex XVII (see section 15)

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Riepe GmbH & Co. KG

Theodor Rosenbaum Str. 28-30

32257 Bünde - Deutschland

Tel.: +49 (0) 5223 - 687407-0

Fax: +49 (0) 5223 - 687407-50

E-Mail: info@riepe.eu

- Informing department:

Tel.: +49 (0) 5223 - 687407-0

E-mail: info@riepe.eu

- 1.4 Emergency telephone number:

Poison Control Center, Mainz

Tel. 00 49 / 61 31 / 19 240

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 1)

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Determination of endocrine-disrupting properties

78-93-3 2-Butanone

List II

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of the substances listed below with harmless additions

- Dangerous components:			
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	50-100%	
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥10-<20%	
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	<i>≥</i> 2.5-<10%	
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	2-Butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≤1%	

- Additional information For the wording of the listed hazard phrases refer to section 16.
- Composition/Ingredients

Constituents according to EC-Regulation 648/2004:

Perfumes (d-Limonene),

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General advice:

Instantly remove any clothing soiled by the product.

In case of unconsciousness bring patient into stable side position for transport.

- After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact

Instantly wash with water and soap and rinse thoroughly. If skin irritation persists, seek medical advice.

- After eye contact

Rinse immediately opened eye for several minutes under running water. Then consult doctor.

- After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; instantly call for medical help.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures. In case of incomplete combustion carbon monoxide can arise. Fumes are heavier than air and distributed over ground. Inflammation is possible from a far distance.

- 5.3 Advice for firefighters
- Protective equipment:

See section 8.

Wear full protective suit with self-contained breathing apparatus.

- Additional information

Endangered containers in the surrounding area should be cooled with a water-hose.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment and keep unprotected persons away.

Extinguish naked flames. Remove flammable sources. No smoking. Avoid sparks. Avoid contact with skin, eyes and clothing. Avoid inhalation of fumes. Air contaminated rooms thoroughly. Protect against electrostatic sparks.

- 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

Inform respective authorities in case product reaches water or sewage system.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Danger of explosion

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers.

Ensure good ventilation/exhaustion at the workplace. Avoid repeated or long-term skin contact.

Prevent formation of aerosols.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage

Protect against direct sunlight, other sources of heat and ignition.

Store in cool, dry conditions in well sealed containers.

- Requirements to be met by storerooms and containers:

Observe official regulations on storage and handling of water harzardous substances

- Information about storage in one common storage facility:

Pay attention to regulations / technical guidelines on mixed storage of flammable liquids.

- Further information about storage conditions:

Pay attention to regulations/technical rules for the storage of combustible liquids.

Store in cool, dry conditions in well sealed containers.

- Storage class 3 (VCI Konzept, 2007)
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

-	8.1	Control	parameters
---	-----	---------	------------

-		lues that require monitoring at the workplace:		
67-64-1 ad				
IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm				
78-93-3 2-	Butanone			
IOELV (EU		: 900 mg/m³, 300 ppm		
	Long-term value.	: 600 mg/m³, 200 ppm		
DNELs				
64-17-5 et	hanol			
Oral	DNEL (population)	87 mg/kg bw/day (Long-term, systemic effects)		
Dermal	DNEL (worker)	8,238 mg/kg bw/day (Long-term, systemic effects)		
Inhalative	DNEL (worker)	380 mg/m³ (Long-term, systemic effects)		
	DNEL (population)	114 mg/m³ (Long-term, systemic effects)		
67-64-1 ad	etone			
Oral	DNEL (population)	62 mg/kg bw/day (Long-term, systemic effects)		
Dermal	DNEL (worker)	186 mg/kg bw/day (Long-term, systemic effects)		
	DNEL (population)	62 mg/kg bw/day (Long-term, systemic effects)		
Inhalative	DNEL (worker)	2,420 mg/m³ (Acute, local effects)		
		1,210 mg/m³ (Long-term, systemic effects)		
	DNEL (population)	200 mg/m³ (Long-term, systemic effects)		
67-63-0 pi	opan-2-ol			
Oral	DNEL (population)	26 mg/kg bw/day (Long-term, systemic effects)		
Dermal	DNEL (worker)	888 mg/kg bw/day (Long-term, systemic effects)		
	DNEL (population)	319 mg/kg bw/day (Long-term, systemic effects)		
Inhalative	DNEL (worker)	500 mg/m³ (Long-term, systemic effects)		
	DNEL (population)	89 mg/m³ (Long-term, systemic effects)		
78-93-3 2-	Butanone			
Oral	DNEL (population)	31 mg/kg bw/day (Long-term, systemic effects)		
Dermal	DNEL (worker)	1,161 mg/kg bw/day (Long-term, systemic effects)		
	DNEL (population)	412 mg/kg bw/day (Long-term, systemic effects)		

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

			(Contd. of par	
Inhalative	DNEL	(worker)	600 mg/m³ (Long-term, systemic effects)	
		(population)		
- PNECs				
64-17-5 et	thanol			
PNEC war	ter	2.75 mg/l (int	termittent releases)	
		0.96 mg/l (fre	•	
		0.79 mg/l (ma	arine water)	
PNEC sec	diment	3.6 mg/kg dv	v (freshwater)	
		2.9 mg/kg dv	v (marine water)	
PNEC soil	1	0.63 mg/kg a	lw (soil)	
PNEC ST	P	580 mg/l (se	wage plant)	
67-64-1 a	cetone			
PNEC war	ter	10.6 mg/l (fre	eshwater)	
		1.06 mg/l (ma	arine water)	
PNEC 21 mg/l (intermittent releases)		rmittent releases)		
100 mg/l (sewage plant)		100 mg/l (se	wage plant)	
PNEC sediment 30.4 mg/kg dw (freshwater)		lw (freshwater)		
3.04 mg/kg dw (marine water)		lw (marine water)		
PNEC soil		29.5 mg/kg a	lw (soil)	
67-63-0 p	-			
PNEC war	ter	140.9 mg/l (fl	•	
		• ,	narine water)	
PNEC			rewage plant)	
PNEC sec		0 0	w (freshwater)	
			w (marine water)	
PNEC		140.9 (intermittent releases)		
PNEC soil		28 mg/kg (soil)		
78-93-3 2-Butanone				
PNEC water 55.8 mg/l (freshwater)		•		
		55.8 mg/l (ma	,	
PNEC sec			g dw (freshwater)	
			dw (marine water)	
PNEC soil 22.5 mg/kg dw (soil)		• •		
PNEC STP 709 mg/l (sewage plant)				

- Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls

Room ventilation i.e. vacuum suction. Measures to be taken against electro-static sparks.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Keep away from food, beverages and fodder.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Gases, fumes and aerosols should not be inhaled.

Revision: 17.11.2022 Printing date 17.11.2022 Version number 111.01

Trade name LP 163/93

(Contd. of page 5)

- Breathing equipment: Use breathing protection in case of insufficient ventilation.
- Recommended filter device for short term use: Combination filter A-P2
- Hand protection Protective gloves.
- Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

Material of gloves is recommended for a short-term single use to protect from splashes. For permanent usage contact manufacturer of gloves.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Eye glasses with side protection (EN 166)
- Body protection:

Standard proctective clothing. Chemical resistant safety-shoes or boots. If skin contact is possible, wear inpenetrable protective clothing against this solvent.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour: Red

- Smell: Characteristic - Odour threshold: Not determined.

- Melting point/freezing point: 80 °C

- Boiling point or initial boiling point and boiling

>65 °C

- Lower and upper explosion limit

- Lower: 2.5 Vol % (EN 1839) - Upper: 15 Vol % (etanol)

- Flash point: <21 °C

425 °C (etanol) - Ignition temperature: - Decomposition temperature: Not determined. Not applicable. - pH Not determined.

- pH-value (500 g/l) at 20 °C: 7-9

- Viscosity:

- Kinematic viscosity Not determined. - dynamic: Not determined.

- Solubility

- Water: Soluble

- Partition coefficient n-octanol/water (log value) Not determined.

247 hPa (67-64-1 acetone) - Vapour pressure at 20 °C:

- Density and/or relative density

- Density at 20 °C 0.81 g/cm³ - Relative density Not determined. - Vapour density Not determined.

(Contd. on page 7)

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 6)

- 9.2 Other	information
-------------	-------------

- Appearance:

- Form: Fluid

- Important information on protection of health and environment, and on safety.

- Evaporation rate Not determined.

-Information with regard to physical hazard

classes

- Explosives Void
 - Flammable gases Void
 - Aerosols Void
 - Oxidising gases Void
 - Gases under pressure Void

- Flammable liquids

Highly flammable liquid and vapour.

- Flammable solids
- Self-reactive substances and mixtures
- Pyrophoric liquids
- Pyrophoric solids
- Pyrophoric solids
- Self-heating substances and mixtures
- Substances and mixtures, which emit flammable gases in contact with water
- Oxidising liquids

Void

- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

To avoid: warmth, flames, sparks

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products:

Formation of carbon monoxide and carbon dioxide in case of fire.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50	- LD/LC50 values that are relevant for classification:			
64-17-5 e	ethanol			
Oral	LD50	10,470 mg/kg (rat) (OECD 401)		

(Contd. on page 8)

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

		(Contd. of page 7)	
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC 50 / 4 h	>50 mg/l (rat) (OECD 403)	
		>20 mg/l (mouse)	
67-64-1 ad	cetone		
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	7,426-15,800 mg/kg (rbt)	
Inhalative	LC 50 / 4 h	76 mg/l (rat)	
67-63-0 pi	67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (rat) (OECD 401)	
		4,570 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
		13,400 mg/kg (rab)	
Inhalative	LC 50 / 4 h	30 mg/l (rat)	
78-93-3 2-	78-93-3 2-Butanone		
Oral	LD50	3,300 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rbt)	
Inhalative	LC 50 / 4 h	34.5 mg/l (rat)	
		40 mg/l (mus)	

- Skin corrosion/irritation Less irritating. Remove lipid skin-film.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

- STOT-repeated exposure:		
64-17-5 ethanol		
Oral NOAEL 1,760 mg/kg (rat) (OECD 408, 90 d, target organ: liver)		
67-64-1 acetone		
Oral NOAEL 900 mg/kg (rat) (KG/day 90 days)		
67-63-0 propan-2-ol		
Oral NOAEL 900 mg/kg (rat) ((90d) OECD 408)		

- 11.2 Information on other hazards

- Endocrine disrupting properties	
78-93-3 2-Butanone	List II

EUE -

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 8)

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:				
64-17-5 etha	64-17-5 ethanol			
LC 50 / 48 h	8,140 mg/l (Leuciscus idus)			
EC 50 / 48 h	>10,000 mg/l (Daphnia magna)			
EC 50 / 72 h	275 mg/l (Chlorella vulgaris) (OECD 201)			
67-64-1 acet	one			
LC 50 / 96 h	7,500 mg/l (Leuciscus idus)			
	5,540 mg/l (Oncorhynchus mykiss)			
EC 50 / 48 h	8,800 mg/l (Daphnia magna)			
EC 50 / 96 h	8,300 mg/l (Lepomis macrochirus)			
	7,500 mg/l (Selenastrum capricornutum)			
67-63-0 prop	oan-2-ol			
LC 50 / 96 h	>10,000 mg/l (Pimephales promelas) (OECD 203 (Acute toxicity - fish))			
LC 50 / 48 h	>100 mg/l (Leuciscus idus)			
EC 50 / 48 h	>100 mg/l (Daphnia magna)			
EC 50 / 16 h	1,050 mg/l (Pseudomonas putida) (DIN 38412 T.8)			
EC 50 / 72 h	>100 mg/l (Scenedesmus subspicatus)			
78-93-3 2-Bu	itanone			
LC 50 / 96 h	>3,000 mg/l (fish)			
EC 50 / 48 h	1,382 mg/l (Daphnia)			

- 12.2 Persistence and degradability

67-63-0 propan-2-ol

Biodegradability 49 % /BOD/ThBOD

Biodegradability 53 % /5 d, BSB5/CS (92/69/EG (L383) C.5 * Abbaubarkeit)

CSB 2.23 mg O2/g (Methode : Verordnung (EC) Nr. 440/2008, Anhang, C.)
BSB5 1.72 mg O2/g (Methode : Verordnung (EC) Nr. 440/2008, Anhang, C.)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects

- Respiratory inhibition of communal activated sludge EC 20 (mg/l according to ISO 8192 B):

64-17-5 ethanol

EC 50 (static) >100 mg/l (Chlorella pyrenoidosa) (OECD 201)

- Additional ecological information:
- General notes:

Do not allow to enter drainage system, surface or ground water Water hazard class 1 (Self-assessment): slightly hazardous for water.

EUE -

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 9)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

The following advice is related to new material and not to any processed products. In case of a mixture with other products other disposal methods may become necessary. If in doubt seek advice from product supplier or from local authorities.

- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. If possible, send to be recycled, otherwise burn or deposit in a certified facility.

- Waste disposal key number:

Since 01/01/99 the waste code numbers have not only been product-related but are also essentially application-related. The valid waste code number of the application can be obtained from the European waste catalogue.

- Uncleaned packagings: Disposal must be made according to official regulations.
- Recommendation:

Rented packaging: After optimal emptying, close immediately and return to the supplier without cleaning. Care should be taken that no other materials get into the packaging.

Other containers: After complete emptying and cleaning, send to be reconditioned or recycled.

Caution: Leftovers in the containers may cause the risk of explosion.

Uncleaned containers should not be perforated, cut or welded.

SECTION 14: Transport information	
- 14.1 UN number or ID number - ADR/RID, IMDG, IATA	UN1993
- 14.2 UN proper shipping name - ADR/RID	1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), ACETONE), special provision 640D
- IMDG - IATA	FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), ACETONE) FLAMMABLE LIQUID, N.O.S. (ETHANOL, ACETONE)
- 14.3 Transport hazard class(es) - ADR/RID - Class - Label	3 (F1) Flammable liquids. 3
- IMDG, IATA - Class - Label	3 Flammable liquids. 3
- 14.4 Packing group - ADR/RID, IMDG, IATA	II .
- 14.5 Environmental hazards: - Marine pollutant:	Not applicable. No
- 14.6 Special precautions for user- Kemler Number:- EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 10)

	(Contd. or page 10)
- Stowage Category	В
- 14.7 Maritime transport in bulk according to IMC instruments) Not applicable.
- Transport/Additional information:	
- ADR/RID - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	1L Código E4 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), ACETONE), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

(Contd. on page 12)

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 11)

- REGULATION (EU) 2019/1148

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS		
67-64-1	acetone	
- Regulation (EC) No 273/2004 on drug precursors		
67-64-1	acetone	3
78-93-3	2-Butanone	3
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors		
67-64-1	acetone	3
78-93-3	2-Butanone	3

- National regulations
- Information about limitation of use:

Employment restrictions concerning young persons must be observed.

- Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

- **VOC (EU)** 785.6 g/l
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- UFI market placements:
- Relevant phrases

Complete wording of hazard statements and risk phrases (H- and R-phrases) mentioned in section 3. These phrases refer to the constituents. The labelling for this product is stated in section 2.

- Department issuing data specification sheet: see item 1: Informing department
- Date of previous version: 17.11.2022
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

LEV. Local Exhaust Ventilation

NOAEL: No Observed Adverse Effect Level

RPE: Respiratory Protective Equipment

RCR: Risk Characterisation Ratio (RCR= PEC/PNEC)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Classification, Labelling and Packaging (Regulation (EC) No. 1272/2008)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

ISO: International Organisation for Standardisation

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

(Contd. on page 13)

Page 13/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022 Version number 111.01 Revision: 17.11.2022

Trade name LP 163/93

(Contd. of page 12)

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- * Data compared to the previous version altered.